







DUFFIN CREEK'S PERFORMANCE

20 16

Wastewater Flow

AVERAGE DAILY FLOW

Average volume of wastewater treated at the Plant each day:

317,731,000 litres

(equivalent to filling 127 Olympic-sized swimming pools)

MAXIMUM DAILY FLOW

The most amount of wastewater that has come into the Plant on a single day¹:

579,279,000 litres

(equivalent to filling 232 Olympic-sized swimming pools)

TOTAL FLOW

The total amount of wastewater that flowed into the Plant over the year:

116 billion litres of water

(equivalent to filling 46,400 Olympic-sized swimming pools)

Number of by-passes, spills or abnormal discharge events²: 0

Solids Processed

Total amount of inflowing solids processed:

35,546 dry tonnes

Amount of solids received and treated from other wastewater treatment plants in York and Durham Regions:

4,104 dry tonnes

¹ The maximum flow is affected by large rain events or melting snow that enters the sewer system through holes and openings in pipes and maintenance hole covers.

² This includes the number of times untreated or partially treated wastewater would miss all or part of the treatment process before release into Lake Ontario. It would also include the number of times untreated or partially treated sewage or sludge spilled out of the treatment processes due to an accident, failure or break.



Amount of solids reused as heat energy:

25,324 dry tonnes

The amount of greenhouse gases avoided by using biosolids as fuel at the Plant and not trucking waste to landfills:

more than 4,800 tonnes

(this is equivalent to taking over 1,000 cars off the road)

Water Quality

	Amount in wastewater entering the Duffin Creek Plant	Limits set by province for amount in water leaving the Duffin Creek Plant	Actual level in water leaving Duffin Creek Plant	Average % removal
Total Phosphorus 4	6.6 mg/L	less than 0.8 mg/L	0.52 mg/L	92.1%5
Total Suspended Solids ⁶	303 mg/L	less than 25 mg/L	7.1 mg/L	97.7%
Biological Oxygen Demand (BOD5) ⁷	217 mg/L	less than 25 mg/L	2.7 mg/L	98.8%

Air Quality

Number of odour complaints received:



Number of odour complaints found to be caused by Plant operations:



- 4 Total Phosphorus is a measure of the total amount of phosphorus in the wastewater in its different forms both particulate (small pieces like small grains in the water) and soluble (phosphorus dissolved in the water). It is used as a measure of Plant performance.
- ⁵ This value changes from year to year, but phosphorus levels in the clear treated wastewater leaving the plant remain well within compliance of provincial regulations.
- 6 Total Suspended Solids (TSS) is the amount of material suspended in a wastewater sample. It is used as a measure of Plant performance.
- 7 BOD5 is a measure of the amount of oxygen needed by living organisms in the wastewater to break down organic material over a period of five days. The plant removes this organic material from the water before it is discharged to the lake.



The Regional Municipality of Durham **Works Department** 605 Rossland Rd. E. Whitby, Ontario, L1N 6A3 905-668-7711 or 1-800-372-1102 durham.ca





The Regional Municipality of York **Environmental Services** 17250 Yonge Street Newmarket, Ontario, L3Y 6Z1 1-877-464-9675 york.ca





