



NOTES:

1. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED.
2. CONCRETE FOR PLANTER WALLS SHALL BE 35MPa AT 28 DAYS, 5-7% AIR ENTRAINED, EXPOSURE CLASS C-1.
3. CONCRETE FOR PLANTER WALL FOUNDATION SHALL BE 32MPa AT 28 DAYS AND BE 5-7% AIR ENTRAINED, EXPOSURE CLASS C-2.
4. 10mm PERFORMED JOINT FILLER, TYPE A, NON-EXTRUDING AND RESILIENT BITUMINOUS COLOUR MATCHED POLYSULFIDE SEALANT.
5. ALL EXPOSED CONCRETE SURFACES TO HAVE A SMOOTH ARCHITECTURAL FINISH.
6. CONNECT SUBDRAIN TO POSITIVE DRAINAGE i.e. STORM, CATCH BASIN MANHOLE EVERY 3 PLANTERS MAXIMUM.

Transportation Services		
<p style="font-weight: bold; margin: 0;">PRE-CAST ARCHITECTURAL BOULEVARD PLANTER LAYOUT</p>		
DATE:	MARCH 2017	SCALE N.T.S.
REV.	X X	SS-201B