


- DROPPED CURB
- TACTILE WALKING SURFACE INDICATOR, SEE STANDARD DRAWING E-6.07
- 70mm UNIT PAVERS WITH POLYMERIC JOINTING SAND
- 50mm HPB
- 125mm C.I.P. REINFORCED / WWM CONCRETE SLAB
- 150mm MIN DEPTH GRANULAR A, COMPACTED TO 98% S.P.D.
- 50mm Ø WEEP HOLE FILLED WITH HIGH PERFORMANCE BEDDING

NOTES:

1. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED
2. THIS DETAIL IS TO BE USED IN CONJUNCTION WITH THE TRAFFIC AND ELECTRICAL CONTRACT DRAWINGS AND DETAILS.
3. POLYMERIC JOINTING SAND TO BE APPLIED FLUSH WITH TOP OF PAVERS
4. POLYMERIC SAND TO BE WATERED AS PER THE MANUFACTURES INSTRUCTIONS
5. UNIT PAVERS NOT SUITABLE FOR POLYMERIC JOINTING SAND SHALL HAVE REGULAR CLEAN JOINTING SAND WITH A SEALER APPLIED, UNLESS OTHERWISE DIRECTED BY THE CONTRACT ADMINISTRATOR
6. CONTROL JOINTS ON CURBS TO BE COVERED WITH A 100mm x 200mm FILTER CLOTH ON THE INSIDE OF CURB TO PREVENT MIGRATION OF JOINTING SAND
7. WELDED WIRE MESH IS TO HAVE A 40-60mm OFFSET FROM ALL SURFACES OF THE CONCRETE. ANY FINISHED CONCRETE WITH EXPOSED STEEL REINFORCEMENT SHALL BE REPLACED.

		Transportation Services
UNIT PAVER CURB RAMP DETAIL		
DATE:	MARCH 2017	SCALE N.T.S.
REV.	X	X
		SS-111