



- ARCHITECTURAL PRECAST PLANTER WALL
- 25mm x 25mm CHAMFER
- 50mm x 25mm REVEAL
- DRAINAGE COMPOSITE
- 12mm BITUMINOUS FIBRE BOARD
- SLOTTED RECESS (TAPERED FROM 20mm TO 10mm)
- 16mm Ø X 150mm LONG GALV. ST. RODS AT 600mm O.C.
- 8mm x 50mm STEEL PLATES AT 600 c/c FASTEN TO CONCRETE WITH 10mm Ø HILTI HY 200 ANCHORS (75mm EMBEDMENT)
- 15M AT 200 c/c VERTICAL, NOMINAL COVER 70MM +/- 20
- 15M AT 200 HORIZONTAL
- ALTERNATE HORIZ LEG OF DWLS
- 3-15M CONTINUOUS
- SUBGRADE, COMPACTED TO 98% S.P.D.

**NOTES**

1. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE NOTED.
2. CONCRETE FOR PLANTER WALLS SHALL BE 35MPa AT 28 DAYS, 5-7% AIR ENTRAINED, EXPOSURE CLASS C-1.
3. CONCRETE FOR PLANTER WALL FOUNDATION SHALL BE 35MPa AT 28 DAYS, 5-7% AIR ENTRAINED, EXPOSURE CLASS C-2.
4. 10mm PERFORMED JOINT FILLER, TYPE A, NON-EXTRUDING AND RESILIENT BITUMINOUS COLOUR MATCHED POLYSULFIDE SEALANT.
5. ALL EXPOSED CONCRETE SURFACE TO HAVE A SMOOTH ARCHITECTURAL FINISH.

		<p><b>Transportation Services</b></p>
<p><b>PRE-CAST ARCHITECTURAL BOULEVARD PLANTER</b></p>		
DATE:	DECEMBER 2016	SCALE N.T.S.
REV.	X	X
<p><b>SS-201A</b></p>		