



- UNIT PAVING AS SPECIFIED - REFER TO PAVING LAYOUT DRAWINGS FOR PAVER TYPE AND PATTERN
- POLYMERIC JOINTING SAND REFER TO NOTES/SPECIFICATIONS
- SOD
- PAVER EDGE STEEL ANGLE RESTRAINT
- 150mm OFFSET FROM EDGE RESTRAINT
- 50mm NO. 8 STONE AS PER ASTM D448
- 50MM DIA. WEEP HOLES FILLED WITH NO. 8 STONE AS PER ASTM D448 OR PEA STONE AT LOWEST ELEVATIONS 2 METRES O/C
- 152x152 MD11.1 x MD11.1 WELDED WIRE MESH (ONLY AT INTERSECTION QUADRANTS/SIGHT TRIANGLE EXTENTS)
- 125mm MIN. CAST-IN-PLACE CONCRETE SLAB, 32 MPa AT 28 DAYS, 5-7% AIR ENTRAINED
- 150mm MIN. GRANULAR 'A' COMPACTED TO 98% S.P.D.

NOTES:

1. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED
2. CONCRETE TO BE 32 MPa AT 28 DAYS, 5-7% AIR ENTRAINED
3. POLYMERIC JOINTING SAND TO BE APPLIED FLUSH WITH TOP OF PAVERS
4. POLYMERIC SAND TO BE WATERED AS PER THE MANUFACTURES INSTRUCTIONS
5. CONTROL JOINTS ON CURBS TO BE COVERED WITH A 100mmx200mm FILTER CLOTH ON THE INSIDE OF CURB TO PREVENT MIGRATION OF JOINTING SAND.
6. WELDED WIRE MESH IS TO HAVE A 60mm OFFSET FROM ALL SURFACES OF THE CONCRETE. ANY FINISHED CONCRETE WITH EXPOSED STEEL REINFORCEMENT SHALL BE REPLACED.
7. CONTROL JOINTS SHALL BE LAID OUT WITH THE JOINTS AT 1500mm O.C WITH AN EXPANSION JOINT EVERY THIRD JOINT.



UNIT PAVERS ON CONCRETE BASE

DATE:	JANUARY 2020	SCALE	N.T.S.
REV.	X	X	SS-100