


NOTES:

1. DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED
2. CONCRETE TO BE 35MPa AT 28 DAYS AND BE 5-7% AIR ENTRAINED.
3. CONTROL JOINTS TO BE LOCATED AT MAXIMUM INTERVALS OF 1.5m OC. CONTROL JOINTS TO BE SAW CUT TO A DEPTH OF 30mm.
4. EXPANSION JOINTS TO BE 12mm BITUMINOUS FIBRE BOARD SET AT 12mm BELOW GRADE AND COLOURED CONCRETE SPLASH FINISHED WITH CONCRETE COLOUR MATCHED POLYSULPHITE SEALANT FLUSH WITH FINISHED STRIP FOR CONCRETE BARRIER GRADE. LOCATE EXPANSION JOINTS EVERY THIRD JOINT AND WHERE CONCRETE MEETS OTHER CURB WITH STANDARD GUTTER HARD SURFACES AND STRUCTURES.
5. COLOURED CONCRETE TO HAVE BROOM FINISH PERPENDICULAR TO DIRECTION OF TRAVEL.
6. CONTROL AND EXPANSION JOINTS TO BE BROOM FINISHED AFTER TOOLED.

		<b>Transportation Services</b>
<b>COLOURED CONCRETE SPLASH STRIP FOR CONCRETE BARRIER CURB WITH STANDARD GUTTER BOULEVARDS</b>		
DATE:	MARCH 2017	SCALE N.T.S.
REV.	X X	<b>SS-105</b>